

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 996 016 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:  
26.04.2000 Bulletin 2000/17

(51) Int Cl.7: G02B 6/44

(21) Application number: 99308351.8

(22) Date of filing: 22.10.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(71) Applicant: BOWTHORPE PLC  
Crawley, West Sussex RH10 2NZ (GB)

(72) Inventor: Foss, Raymond Charles  
Plymouth, PL3 4NX (GB)


(30) Priority: 23.10.1998 GB 9823185  
29.10.1998 GB 9823699  
24.02.1999 GB 9904174

(74) Representative: Evans, Huw David Duncan et al  
Urquhart-Dykes & Lord,  
Three Trinity Court,  
21-27 Newport Road  
Cardiff CF24 0AA (GB)

(54) Optical fibre cable

(57) An optical fibre cable comprises a core 10 formed with a plurality of longitudinally-extending grooves 12, equally spaced-apart around its circumfer-

ence, one or more tubes 14 located within each said groove, each tube containing a plurality of optical fibres 16 and a tubular sheath 18 disposed around the core 10.



**FIG. 1**

EP 0 996 016 A2

## Decripti n

[0001] The present invention relates to an optical fibre cable.

[0002] A number of different types of optical fibre cable are known. One such cable comprises a core member having a tensile member provided along its axis, and formed with typically 6 or 8 V-section slots spaced-apart around its circumference: a number of optical fibres are contained within each slot and enclosed by a tubular sheath applied around the core. In another optical fibre cable, a number of tubes, each containing a number of loose optical fibres, are stranded around a cylindrical core member, which has an axial tensile member: again, the cable is completed by a tubular sheath. These two forms of optical fibre cable have good tensile strength and can include a large number of fibres (typically up to 48 fibres in the slotted-core cable, and up to 144 in the loose-tube cable): however, both cables are of relatively large diameter.

[0003] A further known type of optical fibre cable comprises a core member formed with five or ten longitudinally-extending slots, each slot accommodating a number of ribbons each consisting of a number of fibres disposed side-by-side. However, such ribbon cables are difficult to manage in cable splice organisers, partly because of the fixed orientations of the ribbons.

[0004] A yet further known type of cable, the micro-sheath or micro-bundle cable, comprises a bundle of tubes each containing a number of optical fibres, the bundle of fibre-containing tubes being enclosed within an outer, tubular sheath which incorporates tensile strength members. This cable is of relatively small diameter and can contain larger numbers of fibres than the slotted-core and loose-tube cables: however, it is of limited tensile strength and also offers limited resistance to being crushed.

[0005] We have now devised an optical fibre cable which is of relatively small diameter yet has good tensile strength and resistance to crushing, compared to known optical fibre cables having equivalent numbers of optical fibres.

[0006] In accordance with the present invention, there is provided an optical fibre cable which comprises a core formed with a plurality of longitudinally-extending grooves, equally spaced-apart around its circumference, one or more tubes located within each said groove, each tube containing a plurality of optical fibres, and a tubular sheath disposed around the core.

[0007] The core itself may be arranged to provide the required tensile strength for the cable. For this purpose, the core may be made, for example, of aluminium or aluminium alloy, or of g.r.p. (glass reinforced plastics material), or of a polyimide or aromatic polyamide (such as Kevlar). Instead, the core may be provided with one or more tensile members: for example, the core may be provided with a single tensile member extending longitudinally along its axis; instead, or in addition, the core

may be provided with tensile members positioned adjacent its outer surface (either embedded in the core or located in grooves formed in its outer surface), each of these tensile members being mid-way between a respective pair of the fibre-containing grooves. The tensile members may be formed of metal, preferably steel, or of g.r.p., or of a polyimide or aromatic polyamide (such as Kevlar) for example. Because the tensile members are provided in the core, rather than in the sheath, it is easier to strip the sheath and gain access to the optical fibres. The core itself may be extruded from plastics material, preferably high density polyethylene.

[0008] Preferably the core is formed with three or six fibre-containing grooves, but may instead be formed with four such grooves.

[0009] The arrangement of the core, with three, four or six fibre-containing grooves, provides the structure with inherent resistance to crushing. Each fibre-containing groove is preferably part-circular or arcuate in cross-section: the grooves may be re-entrant at the surface of the core, such that portions of the core along the opposite sides of each groove partially close the groove to help retain the fibre-containing tubes; instead, the grooves may be non-re-entrant or fully open at the surface of the core, to allow a group or cluster of fibre-containing tubes to be inserted during manufacture.

[0010] Preferably the fibre-containing grooves follow paths, along the length of the core, of alternating helical form, the grooves thus extending partly around the core in one rotary direction, then reversing to extend partly around the core in the opposite rotary direction, and so on.

[0011] Where each groove of the cable core contains a cluster of two or more fibre-containing tubes, this cluster of tubes may be enclosed in its own sheath, or may be held together by a tape or other filament wound e.g. spirally around them. Instead, the tubes may be held together by means of an adhesive, preferably an adhesive which allows them to be peeled apart when desired. The enclosing sheaths or the binding tapes or the adhesive of the clusters of fibre-containing tubes may be colour-coded: the individual fibre-containing tubes may also be colour-coded and the individual fibres within each tube may also be colour coded. The arrangement provides a particularly effective coding scheme, in which relatively few colours are needed (corresponding to the maximum number of fibres, typically 12, in each tube).

[0012] Each groove of the core may be filled with gel, grease or other composition to prevent moisture or gas migrating along the cable should the outer sheath of the cable be punctured or split. Each fibre-containing tube may also be filled with such a composition as in present loose tube cables.

[0013] Preferably a moisture barrier is provided around the core. Preferably this comprises a strip of metal foil/plastics laminate applied longitudinally of the core and wrapped around the core so that its opposite longitudinal edges overlap.

**[0014]** The fibre-containing tubes (and the individual sheaths where provided, of each cluster of tubes) are preferably formed of plastics material by extrusion, preferably PVC or polyethylene. These extrusions are typically very thin-walled, such that they may be split and removed easily, even using the fingers only.

**[0015]** Material may be applied around the core which has the property that it swells upon absorbing water, to form a block against the migration of moisture along the cable. This material may be impregnated into a tape (e.g. a cloth tape wrapped around the core).

**[0016]** Embodiments of the present invention will now be described by way of examples only and with reference to the accompanying drawings, in which:

FIGURE 1 is a cross-section through a first embodiment of optical fibre cable in accordance with the present invention;

FIGURES 2 and 3 are cross-sections through modifications of the cable shown in Figure 1;

FIGURE 4 is a cross-section through a second embodiment of optical fibre cable in accordance with the present invention;

FIGURES 5 and 6 are cross-sections through modifications of the cable shown in Figure 4;

FIGURE 7 is a cross-section through a third embodiment of optical fibre cable in accordance with the present invention;

FIGURE 8 is a cross-section through a modification of the cable shown in Figure 7;

FIGURE 9 is a cross-section through a fourth embodiment of cable in accordance with the present invention;

FIGURE 10 is an enlarged cross-section through the core of the cable of Figure 9;

FIGURE 11 is a view of an end portion of a cable in accordance with the present invention, shown with its tensile members fixed to an anchor point; and

FIGURE 12 is a view of an end portion of a cable in accordance with the present invention, showing the use of one of its tensile members to strip the sheath from the core of the cable.

**[0017]** Referring to Figure 1 of the drawings, there is shown an optical fibre cable which comprises an extruded core 10 of plastics material, preferably high density polyethylene, which is generally circular in cross-section and formed with three grooves 12, spaced at 120° intervals. Each groove 12 is generally part-circular or arcuate in cross-section. Each groove 12 contains a single tube 14 which encloses a plurality of optical fibres 16. The cable further comprises an outer, tubular sheath 18 of plastics material, which fits directly around the core 10 and closes the grooves 12. The cable also includes a tensile member 20 extending longitudinally along its axis. The tensile member 20 may comprise a metal wire (e.g. of steel) whether solid or stranded, or a cord formed of g.r.p. (glass reinforced plastics) fibres or a solid fila-

ment of a polyimide or aromatic polyamide (such as Kevlar).

**[0018]** Figures 2 and 3 show cables which are the same as the cable of Figure 1, and of the same outside diameters (typically 7mm), except that the grooves 12 are somewhat larger in order to contain two fibre-containing tubes 14 each (Figure 2) or three fibre-containing tubes 14 each (Figure 3).

**[0019]** Typically, the tubes 14 of the cables shown in Figures 1, 2 and 3 may each contain 4, 6, 8 or 12 fibres. The cables may therefore include a maximum of 36 fibres (Figure 1), 72 fibres (Figure 2) or 108 fibres (Figure 3).

**[0020]** Figure 4 shows a cable of larger diameter than the cables of Figure 1, such that the grooves 12 are able to contain four fibre-containing tubes 14. Instead of a single, axial tensile member, the cable of Figure 4 has three tensile members 22 positioned within grooves 23 in the outer surface of the core, each groove 23 being mid-way between a respective pair of the grooves 12. Preferably the tensile members 22 are free to move radially within their grooves 23, to render the cable easier to bend.

**[0021]** Figures 5 and 6 show cables which are the same as the cable shown in Figure 4, and of the same outside diameters (typically 13mm), except that the grooves 12 are somewhat larger in order to accommodate five fibre-containing tubes 14 each (Figure 5) or six fibre-containing tubes each (Figure 6).

**[0022]** Typically, the tubes 14 of the cables shown in Figures 4, 5 and 6 may each contain 4, 6, 8 or 12 fibres. The cables may therefore include a maximum of 144 fibres (Figure 4), 180 fibres (Figure 5) or 216 fibres (Figure 6).

**[0023]** Figure 7 shows a cable of larger diameter again than the cables of Figures 4, 5 and 6, such that the grooves 12 are able to contain seven fibre-containing tubes 14. The cable has one tensile member 20 extending along the axis of the core, and also three tensile members 22 disposed in grooves 23 in the surface of the core, each groove 23 being mid-way between the main grooves 12. Figure 8 shows a cable which is the same as the cable of Figure 7, and of the same diameter (typically 16mm), except that the grooves 12 are arranged to accommodate eight fibre-containing tubes 14.

**[0024]** Typically, the tubes 14 of the cables shown in Figures 7 and 8 may each contain 4, 6, 8 or 12 fibres. The cables may therefore include a maximum of 252 fibres (Figure 7) or 288 fibres (Figure 8).

**[0025]** Figures 9 and 10 show a further embodiment of cable in accordance with the present invention, comprising an extruded core 10 of plastics material, preferably high density polyethylene, which is generally circular in cross-section and formed with six grooves 12, equally spaced at 60° intervals around its circumference. Each groove 12 contains a cluster of four fibre-containing tubes 14, which are enclosed within a sheath 15. Each groove 12 is generally U-shaped in section and

is accordingly fully-open: this allows the clusters of four fibre-containing tubes 14 to be laid in the respective grooves 12 of the pre-extruded core 10. The core 10 includes a tensile member 20 extending along its axis, preferably comprising a stranded steel member typically 2.5mm in diameter, or a g.r.p. or Kevlar member typically of 3.5mm.

[0026] The cluster-containing grooves 12 follow paths, along the length of the core 10, of alternating helical form, the grooves 12 thus extending partly around the core (typically through 90°) in one rotary direction, then reversing to extend around the core (again typically through 90°) in the opposite rotary direction, and so on: thus, typically there is an angular displacement of 180° over one pitch, the length of which (longitudinally of the cable) may be in the range of 150 to 3000mm. The arrangement provides for easy access to the fibres once the cable sheath is cut away.

[0027] A moisture barrier 24 is provided around the core 10, comprising a strip of aluminium/plastics foil laminate extending longitudinally of the cable and wrapped around the core 10 so that its longitudinal edges overlap, and are then bonded together. Finally, an outer sheath 18 of plastics material is extruded over the foil-wrapped core.

[0028] Because of the provision of six grooves 12 in the core 10 of the cable shown in Figure 9, the fibre-containing tubes 14 can be distributed better around the circumference of the core, the grooves 12 being accordingly of lesser depth (for accommodating the same number of fibre-containing tubes) and so allowing space for an axial tensile member 20 of greater diameter and therefore greater strength.

[0029] In each of the above-described cables, the grooves 12 are preferably filled with a gel, grease or other composition so that, should the outer sheath and moisture barrier become split, neither moisture nor gas is able to migrate along the cable. The sheath 15 of each cluster of fibre-containing tubes 14 (Figure 9) may also be filled with such a composition: the fibre-containing tubes 14 of all embodiments may also be filled with such a composition.

[0030] In each of the above-described embodiments, the fibre-containing tubes 14 (and the sheaths 15 of each cluster in Figure 9) are formed of plastics material by extrusion, preferably PVC or polyethylene, and are very thin-walled, such that they may be split and removed easily, even using the fingers only.

[0031] Also in each of the above-described embodiments, the core may be wrapped with a tape (e.g. applied longitudinally so that its opposite edges overlap) which is coated or impregnated with a substance having the property that it swells upon absorbing water, to form a block against the migration of moisture along the cable.

[0032] Referring to Figure 11, for a cable having tensile members 22 in respective grooves 23 at the outside surface of the core, as in the cables of Figures 4 to 8,

these tensile members may be fixed to a common anchor point 30 at the end of the cable, once an end length of the outer sheath 18 and core 10 has been cut back as shown. The fibre-containing tubes 14 are however fully accessible in that they fan out through the spaces between the tensile members 22.

[0033] As shown in Figure 12, any one of the tensile members 22 may be used as a rip cord, pulling it radially outwardly and at the same time longitudinally along the cable from its end, in order to tear the outer sheath 18 along a corresponding longitudinal line T. Once the sheath 18 has been torn in this manner along a sufficiently long line, the sheath 18 can be cut circumferentially to remove the corresponding end length of sheath from the core 10. Although in the embodiments of Figures 4 to 8 the tensile members 22 are located in respective grooves 23 in the core, they may instead be embedded in the core adjacent the outer surface of the latter: each of tensile members 22 can then still be used as a rip cord as just described. Moreover, where the tensile strength of the cable is provided by the core itself (e.g. where this is made of aluminium) or by an axial tensile member 20, the members 22 may be provided to serve as rip cords but without imparting tensile strength.

[0034] Once the outer sheath 18 and core 10 have been cut back, each exposed cluster of fibre-containing tubes 14 may have a sleeve fitted over it, and the end of this sleeve may be pushed into the exposed end of the respective groove 12 in the core for retention.

[0035] In any of the above-described embodiments of cable where each groove 12 of the core contains two or more fibre-containing tubes 14, these tubes may be enclosed in a sheath 15 (as in Figure 9) or held together as a cluster by a tape wound around them. Alternatively, the tubes may be held together by a low-tack adhesive, which may be applied at intervals along their length: in this way, the tubes remain together as a cluster once the sheath 18 is stripped off the core; however, the adhesive enables the tubes to be separated as and when required and even held back together again. The fibres within each tube may likewise be held together by a low-tack adhesive, again possible applied at intervals. The use of such adhesive for the fibres and/or the fibre-containing tubes makes it easier to route the fibres and/or tubes within a fibre management enclosure, just prior to splicing.

[0036] Preferably the tape wound around each cluster of fibre containing tubes 14, or the adhesive used to hold the tubes together, or the sheath 15 enclosing the tubes 14, may be colour-coded, i.e. different colours may be used for the different grooves 12 of the core. The different fibre-containing tubes 14 of each cluster may be differently coloured: finally, to complete the colour-coding scheme, the individual fibres within each tube may be differently coloured. This colour-coding scheme is particularly effective, because only 12 different colours are required (being the maximum number of fibres per tube

14) for unique identification of all fibres (i.e. by means of the colour of the fibre, the colour of the tube in which it is contained, and the colour assigned to the groove in which its cluster of tubes is contained).

#### Claims

1. An optical fibre cable which comprises a core formed with a plurality of longitudinally-extending grooves, equally spaced-apart around its circumference, one or more tubes located within each said groove, each tube containing a plurality of optical fibres, and a tubular sheath disposed around the core.
2. An optical fibre cable as claimed in claim 1, in which the core is arranged to provide the tensile strength for the cable.
3. An optical fibre cable as claimed in claim 2, in which the core is provided with one or more tensile members extending longitudinally along its axis.
4. An optical fibre cable as claimed in claims 2 or 3, in which the core is provided with tensile members positioned adjacent its outer surface.
5. An optical fibre cable as claimed in any preceding claim, in which the core is formed with three, four or six fibre-containing grooves.
6. An optical fibre cable as claimed in any preceding claim, in which each fibre-containing groove is part-circular or arcuate in cross-section.
7. An optical fibre cable as claimed in any preceding claim, in which the grooves are re-entrant at the surface of the core.
8. An optical fibre cable as claimed in any of claims 1 to 6, in which the grooves are non-re-entrant or fully open at the surface of the core.
9. An optical fibre cable as claimed in any preceding claim, in which the fibre-containing grooves follow paths, along the length of the core, of alternating helical form, the grooves thus extending partly around the core in one rotary direction, then reversing to extend partly around the core in the opposite rotary direction, and so on.
10. An optical fibre cable as claimed in any preceding claim, in which each groove of the cable core contains a cluster of two or more fibre-containing tubes.
11. An optical fibre cable as claimed in claim 10, in which said cluster of tubes is enclosed in its own sheath.
12. An optical fibre cable as claimed in claim 10, in which said cluster of tubes is held together by a tape or other filament wound around them.
13. An optical fibre cable as claimed in claim 10, in which said cluster of tubes is held together by means of an adhesive.
14. An optical fibre cable as claimed in claim 13, in which said cluster of tubes is held together by means of an adhesive which allows them to be peeled apart when desired.
15. An optical fibre cable as claimed in any of claims 10 to 14, in which the enclosing sheaths or the binding tapes or the adhesive of the clusters of fibre-containing tubes are colour-coded.
16. An optical fibre cable as claimed in any preceding claim, in which the individual fibre-containing tubes are colour-coded.
17. An optical fibre cable as claimed in any preceding claim, in which the individual fibres within each tube are colour coded.
18. An optical fibre cable as claimed in any preceding claim, in which the core is filled with a composition to prevent moisture or gas migrating along the cable.
19. An optical fibre cable as claimed in any preceding claim, in which the fibre-containing tube is filled a composition to prevent moisture or gas migrating along the tube.
20. An optical fibre cable as claimed in any preceding claim, in which a moisture barrier is provided around the core.
21. An optical fibre cable as claimed in claim 20, in which the moisture barrier comprises a strip of metal foil/plastics laminate applied longitudinally of the core and wrapped around the core so that its opposite longitudinal edges overlap.
22. An optical fibre cable as claimed in any preceding claim, in which the fibre-containing tubes are formed of plastics material by extrusion.
23. An optical fibre cable as claimed in any preceding claim, in which the fibre-containing tubes are very thin-walled, such that they may be split and removed easily.
24. An optical fibre cable as claimed in any preceding

claim, in which material is applied around the core which has the property that it swells upon absorbing water, to form a block against the migration of moisture along the cable.

5

25. An optical fibre cable as claimed in claim 24, in which said material is impregnated into a tape wrapped around the core.

10

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5







FIG. 6




**FIG. 7**




**FIG. 8**




**FIG. 9**




**FIG. 10**



**FIG. 11**



**FIG. 12**



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 996 016 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
**13.03.2002 Bulletin 2002/11**

(51) Int Cl.<sup>7</sup>: **G02B 6/44**

(43) Date of publication A2:  
**26.04.2000 Bulletin 2000/17**

(21) Application number: **99308351.8**

(22) Date of filing: **22.10.1999**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(71) Applicant: **BOWTHORPE PLC**  
**Crawley, West Sussex RH10 2RZ (GB)**

(72) Inventor: **Foss, Raymond Charles**  
**Plymouth, PL3 4NX (GB)**


(30) Priority: **23.10.1998 GB 9823185**  
**29.10.1998 GB 9823699**  
**24.02.1999 GB 9904174**

(74) Representative: **Evans, Huw David Duncan t al**  
**Urquhart-Dykes & Lord,**  
**Three Trinity Court,**  
**21-27 Newport Road**  
**Cardiff CF24 0AA (GB)**

(54) **Optical fibre cable**

(57) An optical fibre cable comprises a core (10) formed with a plurality of longitudinally-extending grooves (12), equally spaced-apart around its circum-

ference, one or more tubes (14) located within each said groove, each tube containing a plurality of optical fibres (16) and a tubular sheath (18) disposed around the core (10).



**FIG. 1**

**EP 0 996 016 A3**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 8351

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 039 197 A (RAWLYK MICHAEL G) 13 August 1991 (1991-08-13)  * column 4, line 36 - column 5, line 15; figure 4 *	1-3,5,8, 18,20, 21,24,25	G02B6/44
Y		4,6,7, 9-17,19, 22,23	
X	US 5 699 467 A (KOJIMA TORU ET AL) 16 December 1997 (1997-12-16) * column 4, line 53 - column 5, line 10; figures 3,4 *	1,5,8,10	
Y		2-4,6,7, 9,11-19, 22,23	
X	US 4 784 461 A (ABE KOICHI ET AL) 15 November 1988 (1988-11-15) * column 3, line 26 - column 4, line 45; figures 1-3 *	1-3,6,8, 9,18-21	
Y		5,7, 10-17, 22,23	TECHNICAL FIELDS SEARCHED (Int.Cl.7) G02B
Y	US 4 983 013 A (DOTZER PETER ET AL) 8 January 1991 (1991-01-08) * column 4, line 7 - line 13; figure 1 *	2-4	
Y	PATENT ABSTRACTS OF JAPAN vol. 005, no. 126 (P-075), 14 August 1981 (1981-08-14) & JP 56 066805 A (NIPPON TELEGR & TELEPH CORP), 5 June 1981 (1981-06-05) * abstract *	5-7	
-/--			
The present search report has been drawn up for all claims			
Place of search <b>MUNICH</b>		Date of completion of the search <b>4 December 2001</b>	Examiner <b>Lord, R</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1500 03 R2 (P04C01)



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 8351

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	US 5 067 791 A (NISHIYAMA SATOSHI) 26 November 1991 (1991-11-26) * the whole document *	6,15-17	
Y	PATENT ABSTRACTS OF JAPAN vol. 014, no. 088 (P-1008), 19 February 1990 (1990-02-19) -& JP 01 297609 A (SUMITOMO ELECTRIC IND LTD), 30 November 1989 (1989-11-30) * abstract; figure 2 *	2,3,6, 9-15,23	
Y	EP 0 498 621 A (BOTTOMS JACK JR ; CARTER CHARLES L (US)) 12 August 1992 (1992-08-12) * column 8, line 7 - column 12, line 29; figure 1 *	5,6,18, 19,22	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Place of search <b>MUNICH</b>		Date of completion of the search <b>4 December 2001</b>	Examiner <b>Lord, R</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1603 03 82 (P04C01)

# ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 99 30 8351

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-12-2001

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5039197	A	13-08-1991	US	5188883 A	23-02-1993
US 5699467	A	16-12-1997	JP	8329745 A	13-12-1996
			CA	2178283 A1	07-12-1996
US 4784461	A	15-11-1988	DE	3786877 D1	09-09-1993
			DE	3786877 T2	05-01-1994
			EP	0266941 A2	11-05-1988
			CA	1277523 A1	11-12-1990
			JP	63141009 A	13-06-1988
US 4983013	A	08-01-1991	AT	101928 T	15-03-1994
			DE	58907028 D1	31-03-1994
			EP	0356786 A2	07-03-1990
			JP	2108011 A	19-04-1990
			JP	2868540 B2	10-03-1999
JP 56066805	A	05-06-1981	NONE		
US 5067791	A	26-11-1991	AU	588459 B2	14-09-1989
			AU	7262587 A	12-11-1987
			CA	1310529 A1	24-11-1992
			DE	3788894 D1	10-03-1994
			DE	3788894 T2	05-05-1994
			EP	0245752 A2	19-11-1987
			KR	9101810 Y1	28-03-1991
JP 01297609	A	30-11-1989	NONE		
EP 0498621	A	12-08-1992	US	5195158 A	16-03-1993
			US	5204926 A	20-04-1993
			AT	151889 T	15-05-1997
			AU	1375192 A	07-09-1992
			BR	9205574 A	11-10-1994
			DE	69218989 D1	22-05-1997
			EP	0498621 A2	12-08-1992
			ES	2103339 T3	16-09-1997
			MX	9200513 A1	01-08-1992
			US	5274725 A	28-12-1993
			WO	9214175 A1	20-08-1992
			MX	9201220 A1	01-07-1993

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82